



## 540 rpm PTO Pumps and Gearbox Selection, Male or Female Quick Release, Threaded Body Pump Ports, Pre Assembled

Part Number	Flow l/min	Input rpm	Cont. Pressure bar	Max Press. bar	Gearbox Shaft PTO	Pump cc/rev	Gearbox Ratio	Pump Group
60004-6+C16X2T1B	32.8	540	190	230	Female Q. R.	16	3.8 : 1	2
60001-6+C16X2T1B	32.8	540	190	230	Male Spline	16	3.8 : 1	2
60004-6+C22X2T1B	46	540	180	220	Female Q. R.	22.5	3.8 : 1	2
60001-6+C22X2T1B	46	540	180	220	Male Spline	22.5	3.8 : 1	2
60004-5+C28X2T1B	52.9	540	140	220	Female Q. R.	28	3.5 : 1	2
60001-5+C28X2T1B	52.9	540	140	220	Male Spline	28	3.5 : 1	2
71004-6+30C28X068NT	57.4	540	200	230	Female Q. R.	28	3.8 : 1	3
71001-6+30C28X068NT	57.4	540	200	230	Male Spline	28	3.8 : 1	3
71004-6+30C32X068NT	65.6	540	200	230	Female Q. R.	33	3.8 : 1	3
71001-6+30C32X068NT	65.6	540	200	230	Male Spline	33	3.8 : 1	3
71004-6+30C36X068NT	73.8	540	200	230	Female Q.R.	38	3.8 : 1	3
71001-6+30C36X068NT	73.8	540	200	230	Male Spline	38	3.8 : 1	3
71004-6+30C42X068NT	86.1	540	200	230	Female Q.R.	38	3.8 : 1	3
71001-6+30C42X068NT	86.1	540	200	230	Male Spline	38	3.8 : 1	3
71004-6+30C46X068NT	94.3	540	180	210	Female Q.R.	44	3.8 : 1	3
71001-6+30C46X068NT	94.3	540	180	210	Male Spline	44	3.8 : 1	3
71004-6+30C55X068NT	112.8	540	180	210	Female Q. R.	55	3.8 : 1	3
71001-6+30C55X68NT	112.8	540	180	210	Male Spline	55	3.8 : 1	3