

# Standard DC Tail lift Packs



12 or 24 DC power units

2.1 cc/rev gear pump

Electric motor power 1.6kw or 2.1kw on 12 VDC, 2.2kw on 24 VDC 3, 5 or 8 Litre Plastic tank

5 or 10 litre Cylindrical Steel tank

Max pressure up to 230 bar

Complete with suction strainer, return oil diff user and filler breather Relief valve is adjustable between 80-250 bar

Normally closed solenoid lowering valve with P line check valve

Part Number	Voltage	Motor Power	Pump displacement	Reservoir capacity litres	Reservoir type
TLP12/3P16	12DC	1600W	2.1 cc/rev	3	Square plastic
TLP12/3P21	12DC	2100W	2.1 cc/rev	3	Square plastic
TLP24/3P22	24DC	2200W	2.1 cc/rev	3	Square plastic
TLP12/5P16	12DC	1600W	2.1 cc/rev	5	Square plastic
TLP12/5P21	12DC	2100W	2.1 cc/rev	5	Square plastic
TLP24/5P22	24DC	2200W	2.1 cc/rev	5	Square plastic
TLP12/5S16	12DC	1600W	2.1 cc/rev	5	Cylindrical steel
TLP12/5S21	12DC	2100W	2.1 cc/rev	5	Cylindrical steel
TLP24/5S22	24DC	2200W	2.1 cc/rev	5	Cylindrical steel
TLP12/8P16	12DC	1600W	2.1 cc/rev	8	Square plastic
TLP12/8P21	12DC	2100W	2.1 cc/rev	8	Square plastic
TLP24/8P22	24DC	2200W	2.1 cc/rev	8	Square plastic
TLP12/10S16	12DC	1600W	2.1 cc/rev	10	Cylindrical steel
TLP12/10S/21	12DC	2100W	2.1 cc/rev	10	Cylindrical steel
TLP24/10S22	24DC	2200W	2.1 cc/rev	10	Cylindrical steel

Options	Description
P0201	2 BUTTON WIRED PENDANT CONTROL
P0202	4 BUTTON WIRED PENDANT CONTROL
F16000001	MOTOR PLASTIC COVER
E60543006	FOOT MOUNTING BRACKET

