



Frame size	A B C D E F G K M N P S T M N P S T M N P S T M N P S T AB BB AC AD HD L																																	
									IM B14				IM B14L				IM B5				IM B5R													
56	90	71	36	9	20	3	7.2	5.8	65	50	80	M5	2.5	85	70	105	M6	2.5	100	80	120	7	3	85	70	105	8	2.5	108	89	110	100	156	195
63	100	80	40	11	23	4	8.5	7	75	60	90	M5	2.5	100	80	120	M6	3	115	95	140	10	3	100	80	120	8	3	120	103	120	109	172	213
71	112	90	45	14	30	5	11	7	85	70	105	M6	2.5	115	95	140	M8	3	130	110	160	10	3.5	115	95	140	10	3	132	104	139	119	189	255
80	125	100	50	19	40	6	15.5	10	100	80	120	M6	3	130	110	160	M8	3.5	165	130	200	12	3.5	130	110	160	10	3.5	160	124	151	135	215	301
90S	140	100	56	24	50	8	20	10	115	95	140	M8	3	130	110	160	M8	3.5	165	130	200	12	3.5	130	110	160	10	3.5	177	125	175	145	235	308
90L	140	125	56	24	50	8	20	10	115	95	140	M8	3	130	110	160	M8	3.5	165	130	200	12	3.5	130	110	160	10	3.5	177	150	175	145	235	360
100L	160	140	63	28	60	8	24	12	130	110	160	M8	3.5	165	130	200	M10	3.5	215	180	250	14.5	4	165	130	200	12	3.5	196	170	196	155	255	372
112M	190	140	70	28	60	8	24	12	130	110	160	M8	3.5	165	130	200	M10	3.5	215	180	250	14.5	4	165	130	200	12	3.5	218	183	219	173	286	394
132S	216	140	89	38	80	10	33	12	165	130	200	M10	3.5	215	180	250	M12	4	265	230	300	14.5	4	215	180	250	14.5	4	252	175	258	192	324	462
132M	216	178	89	38	80	10	33	12	165	130	200	M10	3.5	215	180	250	M12	4	265	230	300	14.5	4	215	180	250	14.5	4	252	218	258	192	324	529
160M	254	210	108	42	110	12	37	15	215	180	250	M12	4						300	250	350	18.5	5	265	230	300	14.5	4	302	304	314	246	406	617
160L	254	254	108	42	110	12	37	15	215	180	250	M12	4						300	250	350	18.5	5	265	230	300	14.5	4	302	304	314	246	406	661

Aluminium three-phase squirrel cage induction motors according to IEC/DIN, multi-mount design with removable feet.
 Voltage 220-240/380-420V or 380-420/660-720V, 50Hz, Insulation class F, Class B Temperature rise, Protection IP55, PTC Fitted as standard, Colour RAL 5010. NSK Bearings and Cast iron drive end shield frame 100 and above.
 Flange motors B5, B14 small available up to and including size 160. B14 large to 132.
 Available in IE1, IE2 and IE3 efficiency. CUS/UL in IE3.